

EXXON REGULAR UNLEADED CG

ExxonMobil
Lubricants &
Petroleum Specialites

DATE ISSUED: 03/15/00
SUPERSEDES DATE: 08/10/99

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

COMPANY: Exxon Mobil Corporation
ExxonMobil Lubricants & Petroleum
Specialties Company
3225 Gallows Road
Fairfax, VA 22037-0001

PRODUCT CODE
000005 - 11351

PRODUCT NAME
EXXON REGULAR UNLEADED CG

THIS PRODUCT DOES NOT MEET THE REQUIREMENTS FOR REFORMULATED GASOLINE AND MAY NOT BE USED IN ANY REFORMULATED GASOLINE COVERED AREA.

This Material Safety Data Sheet is valid for all EXXON UNLEADED REGULAR and UNLEADED REGULAR Conventional Gasolines.

PRODUCT CATEGORY

Conventional Motor Gasoline

MEDICAL EMERGENCY TELEPHONE NUMBER: (713) 656-3424

TRANSPORTATION EMERGENCY TELEPHONE NUMBERS

(BAYTOWN) (281) 834-3296 (CHEMTREC) 1-800-424-9300

Product Information and Technical Assistance: 1-800-443-9966

FAXED MSDSs: 1-800-298-4007 MAILED MSDSs OR OTHER ASSISTANCE: (713) 656-5949

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NO. OF COMPONENTS	APPROXIMATE CONCENTRATION
Product is a variable complex mixture of components, principally hydrocarbons, blended to performance, rather than chemical specifications and typically contains the following:		

Naphtha (petroleum), light catalytic cracked	64741-55-5	
--	------------	--

Naphtha (petroleum), heavy catalytic cracked	64741-54-4	
--	------------	--

Naphtha (petroleum), full-range reformed	68919-37-9	
--	------------	--

Naphtha (petroleum), full-range alkylate	64741-64-6	
--	------------	--

Naphtha (petroleum), sweetened	64741-87-3	
Butane	106-97-8	

Proprietary additives
It may include varying amounts of the following identifiable components:

Benzene	71-43-2	0-4.9%
Cumene	98-82-8	0-1%
Cyclohexane	110-82-7	0-1%
Ethylbenzene	100-41-4	0-3%
Naphthalene	91-20-3	0-1%
n-Hexane	110-54-3	0-3%
Toluene	108-88-3	0-20%
Xylene	1330-20-7	0-10%

1,2,4-Trimethylbenzene	95-63-6	0-2%
It may also include varying amounts of oxygenates such as the following:		
Di-isopropyl ether	108-20-3	0-18%
Ethanol	64-17-5	0-10%
Ethyl-tertiary-butyl ether	637-92-3	0-18.5%
Methyl-tertiary-butyl ether	1634-04-4	0-16%
Tertiary-amyl-methyl-ether	994-05-8	0-18.5%
SEE SECTION 8 FOR EXPOSURE LIMITS		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

OSHA REQUIRED LABEL INFORMATION

In compliance with hazard and right-to-know requirements, where applicable OSHA Hazard Warnings may be found on the label, bill of lading or invoice accompanying this shipment.

DANGER!

EXTREMELY FLAMMABLE

LONG-TERM, REPEATED EXPOSURE MAY CAUSE
CANCER, BLOOD AND NERVOUS SYSTEM DAMAGE

CONTAINS: BENZENE

Note: Product label may contain non-OSHA related information also.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

Health	Flammability	Reactivity	BASIS
1	3	0	Recommended by ExxonMobil

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION

Health	Flammability	Reactivity	BASIS
1	3	0	Recommended by the National Fire Protection Association

VARIABILITY AMONG INDIVIDUALS

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure)

Prolonged or repeated liquid contact with the skin will dry and defat the skin, leading to possible irritation and dermatitis.

High vapor concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE

Benzene - Individuals with liver disease may be more susceptible to toxic effects.

Hexane - Individuals with neurological disease should avoid exposure.

Petroleum Solvents/Petroleum Hydrocarbons - Skin contact may aggravate an existing dermatitis.

4. FIRST AID MEASURES

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial